SAFETY DATA SHEET

1. Identification

Product number 1000002364

480 SCREEN OPENER Product identifier Camie-Campbell, Inc. **Company information** 1000 INTEGRAM DRIVE

PACIFIC, MO 63069 United States

www.camie.com

Company phone General Assistance 1-800-325-9572

Emergency telephone US Emergency telephone outside 1-866-836-8855 1-952-852-4646

01 Version #

Recommended use Not available. **Recommended restrictions** None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 **Health hazards** Acute toxicity, inhalation Category 4 Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2 Carcinogenicity Category 2 Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. Suspected of causing cancer.

Precautionary statement

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If

in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eve irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before

reuse.

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Product name: 480 SCREEN OPENER SDS US 1 / 11 Product #: 1000002364 Version #: 01 Issue date: 09-07-2018

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Solvent Naphtha (petroleum), Ligh Aromatic	t	64742-95-6	20 - 40
1,2,4-trimethylbenzene		95-63-6	10 - 20
Butane		106-97-8	10 - 20
Cyclohexanone		108-94-1	10 - 20
Propane		74-98-6	10 - 20
Xylene		1330-20-7	1 - 2.5
Cumene		98-82-8	0.1 - 1

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or Inhalation artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Severe eye Most important

irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin symptoms/effects, acute and irritation. May cause redness and pain. delayed

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. medical attention and special treatment needed

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware General information of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

media

Alcohol resistant foam. Dry powder. Carbon dioxide (CO2). Suitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire. Unsuitable extinguishing

Contents under pressure. Pressurized container may explode when exposed to heat or flame. Specific hazards arising from During fire, gases hazardous to health may be formed.

the chemical Firefighters must use standard protective equipment including flame retardant coat, helmet with Special protective equipment

and precautions for firefighters face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with Fire fighting equipment/instructions water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

SDS US 2 / 11 Product #: 1000002364 Version #: 01 Issue date: 09-07-2018

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities

Level 3 Aerosol.

US. OSHA Table 7-1 Limits for Air Contaminants (29 CFR 1910.1000)

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Cumene (CAS 98-82-8)	PEL	245 mg/m3	
		50 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
		50 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Cumene (CAS 98-82-8)	TWA	50 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
,	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
1,2,4-trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
,		25 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
•		800 ppm	
Cumene (CAS 98-82-8)	TWA	245 mg/m3	

Product name: 480 SCREEN OPENER

SDS US

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
		50 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
·		25 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values

ACGIH Biological Exposure Indice	ACGIH	Biological	Exposure	Indices
---	--------------	------------	----------	---------

Components	Value	Determinant	Specimen	Sampling Time
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8) Skin designation applies. Cyclohexanone (CAS 108-94-1) Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8)
Cyclohexanone (CAS 108-94-1)
Can be absorbed through the skin.
Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cumene (CAS 98-82-8)

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

Cyclohexanone (CAS 108-94-1)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering

Eye wash facilities and emergency shower must be available when handling this product.

controls

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating,

drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

9. Physical and chemical properties

Appearance

Physical stateGas.FormAerosol.ColorNot available.

Product name: 480 SCREEN OPENER

Product #: 1000002364 Version #: 01 Issue date: 09-07-2018

Not available. Odor Odor threshold Not available. Not available. Hq Not available. Melting point/freezing point

range

Flash point -156.0 °F (-104.4 °C) propellant estimated

Not available.

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Initial boiling point and boiling

1.9 % estimated

Flammability limit - upper

(%)

9.5 % estimated

Explosive limit - lower (%)

Not available. Explosive limit - upper (%) Not available. Not available. Not available.

Relative density

Vapor pressure

Vapor density

Not available.

Solubility(ies)

Solubility (water) **Partition coefficient**

Not available. Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Not explosive. **Explosive properties** Oxidizing properties Not oxidizing. Specific gravity 0.165 estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. Causes skin irritation. Skin contact

Eye contact Causes serious eye irritation.

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin

irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful if inhaled.

Product name: 480 SCREEN OPENER Product #: 1000002364 Version #: 01 Issue date: 09-07-2018 Components Species Test Results

Components	Species	Test nesults
1,2,4-trimethylbenzene (CAS	S 95-63-6)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 3160 mg/kg
	Rat	3440 mg/kg, 24 Hours
Inhalation		
Vapor		
LC50	Mouse, Rat	> 2000 ppm, 12 Hours
LC50	Rat	10200 mg/m3, 4 Hours
Oral		
LD50	Rat	6000 mg/kg
Butane (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		4007 " 100 11" :
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Cumene (CAS 98-82-8)		
<u>Acute</u>		
Dermal	5	
LD50	Rabbit	> 3160 mg/kg, 24 Hours
Inhalation		
LC50	Mouse	2000 ppm, 7 Hours
		10 mg/l, 7 Hours
Oral	_	
LD50	Rat	2260 mg/kg
Cyclohexanone (CAS 108-94	1 -1)	
<u>Acute</u>		
Inhalation	Det	0.0 # 411
LC50	Rat	> 6.2 mg/l, 4 Hours
Oral	Det	4000
LD50	Rat	1620 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
LUOU	iviouse	-
	В.	52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
), Light Aromatic (CAS 64742-95-6)	
Acute		
Dermal	D-I-I-i-	4000 # 0411
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation	В.	5000 / 0 ///
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours

Product name: 480 SCREEN OPENER SDS US

Components	Species	Test Results
Oral		
LD50	Rat	4820 mg/kg
Xylene (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 ml/kg, 4 Hours
		12126 mg/kg, 24 Hours
Inhalation		
LC50	Rat	5922 ppm, 4 Hours
Oral		
LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg
		10 ml/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cumene (CAS 98-82-8) 2B Possibly carcinogenic to humans.

Cyclohexanone (CAS 108-94-1)

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.
3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Cumene (CAS 98-82-8) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in

laboratory animals.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways. **Chronic effects** Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

	Species	Test Results
AS 95-63-6)		
EC50	Daphnia	6.14 mg/L, 48 Hours
LC50	Fathead minnow (Pimephales promela	as) 7.19 - 8.28 mg/l, 96 hours
IC50	Algae	2.6 mg/L, 72 Hours
EC50	Daphnia	0.6 mg/L, 48 Hours
	LC50	EC50 Daphnia LC50 Fathead minnow (Pimephales promela

Product name: 480 SCREEN OPENER

SDS US

Product #: 1000002364 Version #: 01 Issue date: 09-07-2018

Species Test Results Components LC50 Rainbow trout, donaldson trout 2.7 mg/l, 96 hours Fish

(Oncorhynchus mykiss)

Cyclohexanone (CAS 108-94-1)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 481 - 578 mg/l, 96 hours

Xylene (CAS 1330-20-7)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2.89 Butane Cumene 3.66 Cyclohexanone 0.81 Propane 2.36 **Xylene** 3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

> under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) 2.1

Not applicable. Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

N82 **Special provisions** Packaging exceptions 306 Packaging non bulk None None Packaging bulk

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN number UN1950

Aerosols, flammable **UN proper shipping name**

Product name: 480 SCREEN OPENER

^{*} Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions. Cargo aircraft only

LTD QTY

Not applicable.

Allowed with restrictions.

LTD QTY **Packaging Exceptions**

IMDG

UN number UN1950 **UN** proper shipping name **AEROSOLS**

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) None

Packing group Not applicable.

Environmental hazards

Marine pollutant No. F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations**

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Product name: 480 SCREEN OPENER SDS US

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8)

Cyclohexanone (CAS 108-94-1)

Xylene (CAS 1330-20-7)

Listed.

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,2,4-trimethylbenzene	95-63-6	10 - 20	
Xylene	1330-20-7	1 - 2.5	
Cumene	98-82-8	0.1 - 1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Cumene (CAS 98-82-8) Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

1,2,4-trimethylbenzene (CAS 95-63-6)

Butane (CAS 106-97-8) Cumene (CAS 98-82-8)

Solvent Naphtha (petroleum), Light Aromatic (CAS 64742-95-6)

Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

1,2,4-trimethylbenzene (CAS 95-63-6)

Butane (CAS 106-97-8)

Cumene (CAS 98-82-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-trimethylbenzene (CAS 95-63-6)

Butane (CAS 106-97-8)

Cumene (CAS 98-82-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-trimethylbenzene (CAS 95-63-6)

Product #: 1000002364 Version #: 01 Issue date: 09-07-2018

Butane (CAS 106-97-8)

Cumene (CAS 98-82-8)

Product name: 480 SCREEN OPENER

SDS US

10 / 11

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6) Xylene (CAS 1330-20-7)

US. Rhode Island RTK

1,2,4-trimethylbenzene (CAS 95-63-6)

Butane (CAS 106-97-8) Cumene (CAS 98-82-8)

Cyclohexanone (CAS 108-94-1)

Propane (CAS 74-98-6) Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8) Listed: April 6, 2010

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 09-07-2018

Version # 01

United States & Puerto Rico

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

Yes

11 / 11

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Hazard(s) identification: Hazard statement

Composition / Information on Ingredients: Ingredients Accidental release measures: Environmental precautions Handling and storage: Precautions for safe handling

Handling and storage: Conditions for safe storage, including any incompatibilities

Toxicological information: Carcinogenicity Toxicological information: Chronic effects Toxicological information: Inhalation Ecological information: Ecotoxicity

GHS: Classification

Product name: 480 SCREEN OPENER SDS US

Product #: 1000002364 Version #: 01 Issue date: 09-07-2018

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).