

# Safety Data Sheet

Classified in accordance 29 CFR 1910.1200

## 1. Product Identification

**Product Information:** 1000009767

**Product Identifier:** AUTO BODY RUBBERIZED UNDERCOATING SPRAY

**Recommended Use:** Coating

**Manufacturer/Importer/Distributor Information:** PLZ Corp.  
2651 WARRENVILLE RD, STE 300  
DOWNERS GROVE, IL 60515

800-332-9000

**Emergency Telephone:** 1-800-424-9300

**Restrictions on Use:**  
None

## 2. Hazard(s) identification

### Classification

Aerosol, category 1  
Aspiration Hazard, category 1  
Skin Irritation, category 2  
Eye Irritation, category 2A  
STOT, single exposure, category 3, NE  
Carcinogenicity, category 1A  
Reproductive Toxicity, category 2  
STOT, repeated exposure, category 2

### Label elements

#### HAZARD PICTOGRAMS



### SIGNAL WORD

Danger

### GHS HAZARD STATEMENTS

H222 Extremely flammable aerosol.  
H229 Pressurized container: may burst if heated  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

**GHS PRECAUTIONARY STATEMENTS****Prevention**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe fumes, mists, vapours or spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, eye protection, face protection, and protective clothing

**Response**

P301+P310+P331	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340+P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

**Storage**

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

**Disposal**

P501	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
------	--

**Other Information**

None

**3. Composition/Information on Ingredients****Mixtures**

<u>Chemical Identity</u>	<u>CAS Number</u>	<u>Content in Percent (%)*</u>
Acetone	67-64-1	15-40
Toluene	108-88-3	10-30
Propane	74-98-6	10-30
Xylene	1330-20-7	1-5
Carbon Black	1333-86-4	0.5-1.5
Ethyl Benzene	100-41-4	0.5-1.5
Ethanol	64-17-5	0.1-1.0

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition Comments:** Other components are not hazardous or are below required disclosure limits.

The exact concentration has been withheld as a trade secret.

## 4. First-aid Measures

**SKIN CONTACT:** Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Wash skin thoroughly with soap and water for several minutes. If irritation occurs, get medical attention. Remove contaminated clothing. Launder clothing before re-use.

**EYE CONTACT:** Rinse immediately with plenty of water. Flush eyes with plenty of water for 15 minutes, while holding the eyelids apart. Check victim for contact lenses and remove if present. Get medical attention if irritation persists.

**INHALATION:** Move to fresh air. Remove victim to fresh air. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if you feel unwell.

**INGESTION:** Keep the victim calm and warm. Do NOT induce vomiting. If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Get immediate medical attention.

**IMPORTANT SYMPTOMS:** Inhalation may cause drowsiness or dizziness. Aspiration hazard: Harmful or fatal if swallowed. May cause severe eye irritation. May cause skin irritation. Prolonged or repeated exposure may cause damage to organs.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:** Get medical attention if symptoms occur. Immediate medical attention is required for ingestion.

## 5. Fire-fighting Measures

**EXTINGUISHING MEDIA:** Use fire-extinguishing media appropriate for surrounding materials.

**UNSUITABLE EXTINGUISHING MEDIA:** Do not use water jet as an extinguisher, as this will spread the fire.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Extremely flammable aerosol. Contents under pressure. Keep away from ignition sources and open flames. Prolonged exposure to temperatures above 50°C / 122°F may cause cans to burst. Vapors may travel considerable distance to a source of ignition and flash back. Combustion may produce carbon dioxide and carbon monoxide.

**SPECIAL FIREFIGHTING PROCEDURES:** No data available

## 6. Accidental Release Measures

**PERSONAL PRECAUTIONS :** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Leaking cans should be placed in a plastic bag or open pail away from ignition sources until the pressure has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

**ENVIRONMENTAL PRECAUTIONS:** Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

## 7. Handling and Storage

**HANDLING:** Keep away from sources of ignition - No smoking. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

**SAFE HANDLING ADVICE:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

**STORAGE:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

**NFPA 30B:** Aerosol Level 2

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>TLV-TWA</u>	<u>TLV-STEL</u>	<u>PEL-TWA</u>	<u>PEL-CEILING</u>
Acetone	250 ppm	500 ppm	1000 ppm	N.E.
Toluene	20 ppm	N.E.	200 ppm	300 ppm
Propane	N.E.	N.E.	1000 ppm	N.E.
Xylene	20 ppm	N.E.	100 ppm	N.E.
Carbon Black	3 mg/m3	N.E.	3.5 mg/m3	N.E.
Ethyl Benzene	20 ppm	N.E.	100 ppm	N.E.
Ethanol	N.E.	1000 ppm	1000 ppm	N.E.
Crystalline Silica	0.025 mg/m3	N.E.	50 µg/m3	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

**ENGINEERING CONTROLS:** No data available

### Personal Protection

**EYE/FACE PROTECTION:** Wear goggles/face shield. Chemical safety goggles should be worn where contact is possible.

**SKIN PROTECTION:** Wear impervious gloves to prevent skin contact.

**RESPIRATORY PROTECTION:** Seek advice from local supervisor. In case of inadequate ventilation use suitable respirator.

**HYGIENIC PRACTICES:** When using do not smoke. Observe good industrial hygiene practices.

## 9. Physical and Chemical Properties

### Appearance:

Physical State:	Liquid
Form:	Spray Aerosol
Color:	Black
Odor:	No data available
Odor Threshold:	No data available
pH:	No data available
Freeze Point, °C:	No data available
Boiling Point, °C:	7
Flash Point, °C:	Not applicable to aerosols
Flammability (solid, gas):	Flammable Aerosol
Evaporation Rate:	No data available
Combustibility:	Supports Combustion
Explosive Limits, %:	0.6 - 19.0
Vapor Pressure @20°C, PSI:	50-70
Relative Vapor Density:	Heavier than Air
Relative Density:	0.935
Solubility in Water:	No data available
Partition Coefficient, n-octanol/water:	No data available
Auto-Ignition Temperature, °C:	No data available
Decomposition temperature, °C:	No data available
Kinematic Viscosity:	< 14 mm <sup>2</sup> /s or cSt
Particle Characteristics:	
Size Range, microns (µm):	No data available
Percent under 10 microns:	No data available

## 10. Stability and Reactivity

**REACTIVITY:** Not reactive under normal conditions of use.

**STABILITY:** Material is stable under normal conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:** No data available

**CONDITIONS TO AVOID:** Keep away from heat, sparks, flames, and other sources of ignition. Do not puncture or incinerate containers. Dropping containers may cause bursting.

**INCOMPATIBILITY:** No data available

**HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion may produce carbon dioxide and carbon monoxide.

## 11. Toxicological Information

### Information on Likely Routes of Exposure

**SKIN CONTACT EFFECTS:** May cause irritation, drying, defatting of the skin and dermatitis.

**EYE CONTACT EFFECTS:** Contact may cause severe irritation with redness, tearing and pain.

**INHALATION EFFECTS:** May cause central nervous system effects with drowsiness and dizziness.

**INGESTION EFFECTS:** Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal.

**The following Chemicals are listed on IARC Monographs on the Evaluation of Carcinogenic Risk to Humans:**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>IARC Listing</u>
1333-86-4	Carbon Black	IARC Group 2B,
100-41-4	Ethyl Benzene	IARC Group 2B,
64-17-5	Ethanol	IARC Group 1,
14808-60-7	Crystalline Silica	IARC Group 1,

**The following Chemicals are listed on the U.S. National Toxicology Program (NTP) Report on Carcinogens:**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>NTP Listing</u>
64-17-5	Ethanol	NTP Known Human Carcinogen
14808-60-7	Crystalline Silica	NTP Known Human Carcinogen

**The following Chemicals are listed on U.S. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>OSHA Listing</u>
1333-86-4	Carbon Black	Present
100-41-4	Ethyl Benzene	Present
64-17-5	Ethanol	Present
14808-60-7	Crystalline Silica	Present

The following values are calculated based on chapter 3.1 of the GHS document. The product itself has not been tested.

**ATE ORAL** 24,285 mg/kg

**ATE DERMAL** 10,200 mg/kg

**ATE INHALATION** 206 mg/kg

**Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
67-64-1	Acetone	5,800 mg/kg	7,426 mg/kg	50.1 mg/l
108-88-3	Toluene	5,580 mg/kg	5,000 mg/kg	28.1 mg/l
74-98-6	Propane	5,000 mg/kg	5,000 mg/kg	100 mg/l
1330-20-7	Xylene	3,523 mg/kg	1,100 mg/kg	11 mg/l
1333-86-4	Carbon Black	8,000 mg/kg	5,000 mg/kg	100 mg/l
100-41-4	Ethyl Benzene	3,500 mg/kg	5,000 mg/kg	11 mg/l
64-17-5	Ethanol	10,470 mg/kg	17,100 mg/kg	124.7 mg/l
14808-60-7	Crystalline Silica	5,000 mg/kg	5,000 mg/kg	N.I.

N.I. = No Information

**Skin Corrosion & Irritation:**

<b>Product:</b>	No data available		
<b>Components:</b>			
Toluene	108-88-3	Causes skin irritation.	
Xylene	1330-20-7	Causes skin irritation.	

**Serious Eye Damage & Irritation:**

<b>Product:</b>		No data available
<b>Components:</b>		
Acetone	67-64-1	Causes serious eye irritation.

**Respiratory or Skin Sensitization:**

<b>Product:</b>	No data available
-----------------	-------------------

**STOT-Single Exposure:**

<b>Product:</b>		No data available
<b>Components:</b>		
Toluene	108-88-3	May cause drowsiness or dizziness.
Acetone	67-64-1	May cause drowsiness or dizziness.

**STOT-Repeated Exposure:**

<b>Product:</b>		No data available
<b>Components:</b>		
Toluene	108-88-3	May cause damage to organs through prolonged or repeated exposure.
Ethyl Benzene	100-41-4	May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:**

<b>Product:</b>		No data available
<b>Components:</b>		
Toluene	108-88-3	May be fatal if swallowed and enters airways.
Ethyl Benzene	100-41-4	May be fatal if swallowed and enters airways.

**Carcinogenicity:**

<b>Product:</b>		No data available
<b>Components:</b>		
Crystalline Silica	14808-60-7	May cause cancer

**Reproductive Toxicity:**

<b>Product:</b>		No data available
<b>Components:</b>		
Toluene	108-88-3	Suspected of damaging fertility or the unborn child.

**Germ Cell Mutagenicity:**

<b>Product:</b>	No data available
-----------------	-------------------

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** No data available

**PERSISTENCE:** No data available

**BIOACCUMULATE:** No data available

**MOBILITY IN SOIL:** No data available

**OTHER ECOLOGICAL:** No data available

## 13. Disposal Information

**DISPOSAL INFORMATION:** Consult with your local, regional and federal agencies for information on proper disposal.

**CONTAMINATED PACKAGING :** Consult with your local, regional and federal agencies for information on proper disposal.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No data available

**DOT**

**UN Number:** UN1950  
**Proper Shipping Name:** AEROSOLS, FLAMMABLE  
**Technical Name:** N/A  
**Hazard Class(es)**  
**Class:** 2.1  
**Subsidiary Risk** N/A  
**Packing Group:** N/A

**IATA**

**UN Number:** UN1950  
**Proper Shipping Name:** AEROSOLS, FLAMMABLE  
**Technical Name:** N/A  
**Hazard Class(es)**  
**Class:** 2.1  
**Subsidiary Risk:** N/A  
**Packing Group:** N/A

**IMDG**

**UN Number:** UN1950  
**Proper Shipping Name:** AEROSOLS, FLAMMABLE  
**Technical Name:** N/A  
**Hazard Class(es)**  
**Class:** 2.1  
**Subsidiary Risk:** N/A  
**Packing Group:** N/A

The classification shown in this section may be eligible for use of an exception, such as 'Limited Quantity', per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

<b>15. Regulatory Information</b>
-----------------------------------

**SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.	Wt %
Toluene	108-88-3	14.27
Xylene	1330-20-7	4.26
Ethyl Benzene	100-41-4	1.08

**CHEMICAL INVENTORY STATUS:**

**TSCA** On or in compliance with the inventory

**DSL** All ingredients in this product are listed on the DSL or are exempt.

**CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIVE TOXINS:**



## WARNING

This product can expose you to chemicals including Carbon Black, Ethyl Benzene, Crystalline Silica, which are known to the State of California to cause cancer, and Toluene which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

<u>Chemical Name</u>	<u>CAS-No.</u>
Toluene	108-88-3
Carbon Black	1333-86-4
Ethyl Benzene	100-41-4
Crystalline Silica	14808-60-7

## 16. Other Information

Revision Date: 5/14/2025

Datasheet produced by: Regulatory Department

### Legend

N/A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

TLV - Threshold Limit Values (TLVs®), as established by the American Conference of Governmental Industrial Hygienists (ACGIH®)

PEL - Permissible Exposure Limit, as established by the U.S. Occupational Safety and Health Administration (OSHA), as amended

TSCA - U.S. Toxic Substance Control Act

DSL - Canada Environmental Protection Act: Domestic Substance List

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where the product use and frequency of exposure exceeds that established for the labeled consumer use.

### Further Information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the manufacturer's and seller's control. Purchaser and user are responsible for determining the suitability of the product for a particular purpose, adopting precautions for the protection of property and persons, and compliance with all Federal, State, Provincial, and Local laws.