SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

| Product ID: | 495545 | | | | |
|------------------------|---|------------------|--------------|--|--|
| Product Name: | Zenatize Disinfectant Fresh Scent - 498-179-74424 | | | | |
| Revision Date: | Mar 08 2023 | Date Printed: | Mar 08, 2023 | | |
| Version: | 3.0 | Supersedes Date: | Dec 03, 2018 | | |
| Manufacturer's Name: | Zenex International | | | | |
| Address: | 1 Zenex Circle Cleveland, OH, US, 44146 | | | | |
| Emergency Phone: | 1-800-535-5053 | | | | |
| Information Phone Numb | er: (440)-232-4155 | | | | |
| Fax: | | | | | |
| Product/Recommended L | Jses: Disinfectant | | | | |

SECTION 2) HAZARDS IDENTIFICATION

Classification

Aerosols - Category 2

Gases Under Pressure - Liquefied Gas

Eye Irritation - Category 2A

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 0.69%

Pictograms



Signal Word

Warning

Hazardous Statements - Physical

H223 - Flammable aerosol.

H280 - Contains gas under pressure; may explode if heated.

Hazardous Statements - Health

H319 - Causes serious eye irritation.

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use.

P280 - Wear eye and face protection.

P264 - Wash face, hands and any exposed skin thoroughly after handling.

Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P403 - Store in a well-ventilated place.

Precautionary Statements - Disposal

No data available.

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

| CAS | Chemical Name | % By Weight |
|----------|---------------|-------------|
| 64-17-5 | ETHYL ALCOHOL | 30% - 35% |
| 106-97-8 | BUTANE | 10% - 15% |
| 74-98-6 | PROPANE | 1% - 5% |

See label for active ingredient information. The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4) FIRST-AID MEASURES

Inhalation

If overcome by vapor, move person to fresh air.

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin Contact

Wash with soap and water. If irritation develops, consult a physician .

Ingestion

Ingestion from an aerosol product is unlikely to occur.

Most important symptoms and effects, both acute and delayed

Symptom

Acute, Deliberate inhalation of concentrated vapor or mist may cause headaches. Prolonged and repeated contact with the eyes may cause mild irritation.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2 or water spray.

Unsuitable Extinguishing Media

Use water spray or fog; do not use straight streams.

Specific Hazards in Case of Fire

Containers are under pressure. Temperatures above 130 °F may cause cans to burst. Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

Sensitivity to Mechanical Impact: Content under pressure keep away from heat and open flame. Sensitivity to Static Discharge: Keep away from heat, spark, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity.

Protective equipment and precautions for firefighters

Use personal protective equipment as required.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Methods for and material for containment and cleaning up

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material. Clean contaminated surface thoroughly.

Recommended Equipment

Wear appropriate protective equipment (see Section 8).

Personal Precautions

CONTENTS UNDER PRESSURE. Do not puncture or incinerate cans. Keep out of reach of children.

Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). See section 12 for Ecological Information.

SECTION 7) HANDLING AND STORAGE

General

Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Store in a cool, dry place away from heat and open flame. Avoid storing at below-freezing temperatures. AEROSOL STORAGE LEVEL I (NFPA-30B).

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Safety glasses to guard against splashing.

Skin Protection

Household type gloves, if desired.

Respiratory Protection

None required if used in a well-ventilated area .

Appropriate Engineering Controls

Use with adequate general or local exhaust ventilation.

| Chemical Name | OSHA TWA (ppm) | OSHA TWA (mg/m3) | OSHA STEL (ppm) | OSHA STEL (mg/m3) | OSHA Tables (Z1, Z2, Z3) | OSHA Carcinogen | OSHA Skin designation | NIOSH TWA (ppm) |
|------------------|-------------------|---------------------|--------------------|----------------------|-----------------------------|--------------------|-----------------------|--------------------|
| BUTANE | | | | | | | | 800 |
| ETHYL ALCOHOL | 1000 | 1900 | | | 1 | | | 1000 |
| PROPANE | 1000 | 1800 | | | 1 | | | 1000 |

| Chemical Name | NIOSH TWA (mg/m3) | NIOSH STEL (ppm) | NIOSH STEL (mg/m3) | NIOSH Carcinogen | ACGIH TWA (ppm) | ACGIH TWA (mg/m3) | ACGIH STEL (ppm) | ACGIH STEL (mg/m3) |
|------------------|----------------------|---------------------|-----------------------|---------------------|--------------------|----------------------|---|-----------------------|
| BUTANE | 1900 | | | | | | 1000 (EX) | |
| ETHYL ALCOHOL | 1900 | | | | | | 1000 | |
| PROPANE | 1800 | | | | | | Simple asphyxiant (D), explosion hazard (EX) | |

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

| Dens | sity | 8.33 lb/gal |
|--------|-------------------------|---|
| Dens | sity VOC | 4.27 lb/gal |
| % V | oc | 51.32% |
| Appe | earance | Hazy, yellow liquid |
| Odor | Threshold | N.A. |
| Odor | Description | Fresh scent |
| pН | | 10.0 - 11.0 |
| Wate | er Solubility | Complete |
| Flam | mability | Temperatures above 120°F may cause cans to burst. |
| Vapo | or Pressure | 101.3 kPa (20°C) |
| Flash | n Point | N.A. This is an aerosol for which Flame Projection is 6-8 inches without flashback. |
| Visco | osity, Kinematic | N.A. |
| Lowe | er Explosion Level | N.A. |
| Uppe | er Explosion Level | N.A. |
| Vapo | or Density | N.A. |
| Relat | tive Density | 0.92 concentrate |
| Melti | ng Point/Freezing Point | N.A. |
| Boilir | ng Point/boiling range | 212°F/100°C Water |
| Deco | emposition Pt | N.A. |
| Auto | Ignition Temp | N.A. |
| Evap | oration Rate | Faster than butyl acetate |
| | | |

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Temperatures above 122°F (50°C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers.

Hazardous Reactions/Polymerization

Temperatures above 130 °F may cause cans to burst with force. Hazardous polymerization does not occur.

Hazardous Decomposition Products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

No data available.

Serious Eye Damage/Irritation

Causes serious eye irritation.

Carcinogenicity

Not known chronic effects based on available information.

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Respiratory/Skin Sensitization

No data available.

Specific Target Organ Toxicity - Single Exposure

No data available.

Specific Target Organ Toxicity - Repeated Exposure

No data available.

Aspiration Hazard

No data available.

Acute Toxicity

No data available.

SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical name | Algae/aquatic plants | Fish | Toxicity to | Crustacea |
|--------------------------|----------------------|---|--|---|
| Ethyl alcohol 64-17-5 | | 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 12.0 -16.0: 96 h Oncorhynchus mykiss mL/L LC50 static | Microorganisms EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min | 2: 48 h Daphnia magna mg/L EC50 Static 9268 -14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 |

Persistence and Degradability

No data available.

Bio-Accumulative Potential

See information below.

| Chemical name | Partition coefficient |
|--------------------|-----------------------|
| Ethyl alcohol | -0.32 |
| 64-17-5 | |
| N-Butane | 2.89 |
| 106-97-8 | |
| Propane 74-98-6 | 2.3 |
| 74-98-6 | |

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Pressurized container: Do not pierce or burn, even after use.

SECTION 14) TRANSPORT INFORMATION

| | U.S. DOT Information | IMDG Information | IATA Information |
|------------------------------|-------------------------|------------------|---------------------|
| UN number: | UN1950 | UN1950 | UN1950 |
| Proper shipping name: | Aerosols | Aerosols | Aerosols, flammable |
| Hazard class: | 2.1 | 2.1 | 2.1 |
| Packaging group: | N.A. | N.A. | N.A. |
| Note / Special Provision: | (LTD QTY) | (LTD QTY) | (LTD QTY) |

SECTION 15) REGULATORY INFORMATION

| CAS | Chemical Name | % By Weight | Regulation List |
|--------------|---------------|-------------|--------------------------------|
| 0000064-17-5 | ETHYL ALCOHOL | 25% - 50% | SARA312, VOC,TSCA, ACGIH, OSHA |
| 0000106-97-8 | BUTANE | 10% - 25% | SARA312, VOC, TSCA, ACGIH |
| 0000074-98-6 | PROPANE | 1% - 5% | SARA312, VOC,TSCA, ACGIH, OSHA |


U.S. EPA Label information

EPA Pesticide registration number 498-179

EPA Statement

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label: CAUTION: May cause eye irritation. Avoid contact with the eyes and skin. Avoid breathing of spray mist. Avoid contamination of foodstuff.

SECTION 16) OTHER INFORMATION



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Revision Date: Mar 08, 2023

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.