

PRODUCT INFORMATION SHEET



One Zenex Circle • Cleveland, Ohio 44146  
Toll Free: 866-217-5100 • Fax: 440-232-5101

# ZenaLube Dry Graphite Lubricant

*Dry Graphic Lubricant*  
**ZENEX NUMBER 496305**

## DESCRIPTION

An ideal, fast-drying, super adhesive film lubricant, bonds instantly to metal, rubber, plastic and most substrates. Protects surfaces from pressure and friction, while creating a dirt repelling barrier to resist water, oils and alkalis. Withstands wide temperature ranges and reduces metal wear and fatigue.

## FEATURES AND BENEFITS

Produces a fast drying lubricant to coat and protect metal and plastic extending the life of moving parts. Provides superior lubrication resistant to water, oils, and chemical attack without attracting dust and dirt. Effectively performs in extreme pressures, high temperatures and where a dry lubricant is required and petroleum products must be avoided. Heat stable from -100°F (-73°C) to +850°F (+454°C).

## APPLICATIONS AND USES

Use on locks, bearings, chains, hinges, spark plugs, engine assembly, automotive and industrial gaskets, wheels, gears, chains, hoists, plant machinery, handling equipment, high temperature equipment, oven, furnace and kiln mechanisms. Exceptional on aluminum, brass, copper, titanium, steel alloys and cast iron.

## DIRECTIONS FOR USE

Shake can well before use. Spray 8-12 inches from surface. Spray a light even film. Wipe off excess with a cloth. Repeat application, second coat gives additional protection. For personal safety, do not use while equipment is energized.

NOTE: May damage some plastics or painted surfaces. Test prior to general use.

## SIZE / AVAILABILITY

16 oz. Aerosol  
Net Weight 12 oz.  
12 per case

## STATE RESTRICTION

None.



**Emergency  
Phone Number  
(800) 535-5053**

HMIS	
HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	B

