

PRODUCT INFORMATION SHEET



One Zenex Circle • Cleveland, Ohio 44146
Toll Free: 866-217-5100 • Fax: 440-232-5101

ZenaLube Ultra

Gel Lubricant

ZENEX NUMBER 496955

DESCRIPTION

This product is a transparent, high pressure lubricant with high adhesive strength. A unique combination of natural and synthetic lubrication agents coupled with a high molecular weight polymer (PTFE) makes this product one of the best available.

FEATURES AND BENEFITS

Lasts longer than conventional lubricants. Withstands severe temperatures. Prevents sticking and freezing of rubber and metal. Works from -30°F to +600°F. Protects chains, cables and gears. Resists water washout. Applies as a thin penetrant and quickly sets to a clear tacky gel.

APPLICATIONS AND USES

Use on open gears, wire ropes and cables, chains and sprockets, and conveyors.

DIRECTIONS FOR USE

Shake well before using. Saturate area to be lubricated.
If necessary, repeat application.

SIZE / AVAILABILITY

20 oz. Aerosol
Net Weight 13 oz.
12 per case

STATE RESTRICTION

None.



**Emergency
Phone Number
(800) 535-5053**

HMIS	
HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

