PRODUCT INFORMATION SHEET



One Zenex Circle • Cleveland, Ohio 44146 Toll Free: 866-217-5100 • Fax: 440-232-5101

Silconex Silicone Lubricant **ZENEX NUMBER 497055**

DESCRIPTION

A clear lubricant and preservative, specially formulated to leave a slippery, continuous film that facilitates a wide range of applications.

FEATURES AND BENEFITS

Non-drying formula lubricates, protects and lengthens life of all rubber parts. Thick viscous film adheres to most surfaces like a magnet. Temperature range works from -58°F to +600°F. Protects metal finish from rust and corrosion.

APPLICATIONS AND USES

This product is designed to penetrate the surface pores of synthetic plastics, rubbers, neoprene, wood, fabrics, etc.

DIRECTIONS FOR USE

Shake well before using. Clean surface thoroughly. Spray light film on surface. If used on sticking parts, work back and forth and reapply.


SIZE / AVAILABILITY

16 oz. Aerosol Net Weight 9.75 oz. 12 per case

STATE RESTRICTION None.

> Emergency **Phone Number** (800) 535-5053

HMIS	
HEALTH	1
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	А







DANGER: Extremely flammable aerosol. Press tainer may burst if heated. May be fatal if swall enters ainways. Causes skin irritation. Causes seri

Net Wt. 9.75 oz. (276 gra

cause drowsiness or dizziness. May